



C10
Fungicidal Wash
Bio-Stop

Technical Data

Pack Size
25 Litres

Pallet QTY
30 Units

Application Tool
Brush, Roller or Spray

Suitable Substrate
Concrete, Brick, stone and renders

Coverage
0.3 Ltr per M²

Application Temperature
5 °C - 25 °C

Humidity Requirement
Less than 95%

CE



Fast Acting



Long Term Protection



Bio Stop



Ready to Use



High Coverage



Suitable for Hand
or Spray Application

A powerful water based masonry wash containing carefully selected biocides effective against a broad range of bacterial, algal, fungal and mould species.

PRODUCT INFORMATION

C10 Fungicidal wash is a water based masonry wash containing carefully selected biocides effective against a broad range of bacterial, algal, fungal and mould species. It is used as a masonry cleaner and sterilizer to kill green, black and other organic growths on walls and other masonry.

PREPARATION

Organic growths may indicate consistently damp conditions and substandard direct sunlight. Sources of moisture should be identified and rectified to prevent reoccurrence. Condensation, rising damp, faulty plumbing or guttering, etc. should be considered as a possible source. Remove all loose and flaking material by cleaning the surface with a soft bristle brush. If possible power wash the substrate with a suitable power washer.

APPLICATION

Apply C10 Fungicidal wash directly onto the surface using a pressurised knapsack or garden sprayer but can be brushed or roller applied. Ensure the surface is drenched in the wash and has been absorbed into the capillaries of the substrate. C10 Fungicidal wash must be left for a minimum of 48 hrs to take effect and kill the growing moss and unseen spores. Dead growth should be removed by brushing with a steel brush or a suitable power washer.

Do not apply C10 Fungicidal wash in rain or in temperatures below 5°C.



FM 54357

C10

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product

IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- o If frost is forecast, or in wet conditions
- o When Relative Humidity is above 85%
- o In temperatures below +5°C or above +25°C
- o If the elevation is in direct sunlight
- o If the substrate is hot (at or above 30C) or below +5°C
- o Substrate PH must be less than 8
- o Coverage rates are approx. and do not take into account wastage and uneven substrates

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.