

# WETHERTEX

## PP1



**PP1**  
Pre-prep Wash Coat Primer  
*Extra*

**Technical Data**

Pack Size  
10 Litres

Pallet QTY  
30 Units

Application Tool  
Brush, Roller or Spray

Suitable Substrate  
TK11, GRC, X71, Bonded Paint, Dash,  
Roughcast, Render

Drying Time  
3 - 24 Hrs @ 25 - 5° c

Coverage  
85 M<sup>2</sup> per 10 Litres

Application Temperature  
1° c - 25° c for a min of 24 hrs

Humidity Requirement  
Less than 85% for a min of 24 hrs

CE



Water Repellent



Extra Coverage



High Adhesion



Low Temperature Application



Roller or Brush Application



Highly Polymer Modified

A pliolite-based, ready to use low temperature application through coloured, extra high coverage rate and hiding power primer that is highly weather resistant and highly vapour permeable.

### DESCRIPTION

PP1 Prep-Wash Coat Primer is a ready mixed, flexible through coloured penetrating primer to control suction and ensure good key for finish coating.

### PREPARATION

All surfaces must be sound, clean, dry and free of any material which may impair adhesion. Scaffolding must be independently-tied to allow for uninterrupted application. Any faults in the structure, particularly those which may lead to moisture penetration, must be rectified.

### MIXING

PP1 Prep-Wash Coat Primer is supplied ready to use, but may need re-mixing using a suitable paddle mixer to regain correct consistency for application.

### APPLICATION

By roller – submerge the roller totally in the primer to ensure that the roller is fully loaded with material to allow even application without spreading too thinly.

Specification Clauses relating to these products can be found in NBS Section M20 rendering. BS 5262 Code of Practice for External Rendering and BS 8000-10 must be followed

### STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.



## TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

## HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product.

## IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- o If frost is forecast, or in wet conditions
- o When Relative Humidity is above 85%
- o In temperatures below +1°C or above +25°C
- o If the elevation is in direct sunlight
- o If the substrate is hot (at or above 30C) or below +1°C
- o Coverage rates are approx. and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discoloration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.