



SR72
Smart Cream
Nano

Technical Data

Pack Size
25 kg

Pallet QTY
18 Units

Application Tool
Brush, Roller or Spray

Suitable Substrate
Concrete, Brick, stone and renders

Coverage
100 - 200g per M²

Application Temperature
5°c - 25°c

Humidity Requirement
Less than 95%

CE



Long Term Protection Water Repellent Nano Technology

Energy Saving Waterproofing Highly Polymer Modified

A unique waterproofing energy saving smart Cream.
Not only will this product waterproof the building for years to come, but it will also save you energy and money.

PRODUCT INFORMATION

SR72 WetherDry Smart Cream Nano is an aqueous based hydrophobic impregnating agent based on a mixture of silane and siloxane. SR72 is a high quality speciality product for hydrophobic impregnation of natural mineral substrates.

PREPARATION

All surfaces should be clean, reasonably dry and free from algae, lichen & other growths and grease. If there is evidence of organic growth, power wash to remove & apply Wetherdry C10 Fungicidal wash in accordance with instructions.

MIXING

SR72 WetherDry Smart Cream is supplied ready to use.

APPLICATION

SR72 WetherDry Smart Cream Nano is best applied to the mineral substrate by the airless technique, undiluted and in the desired thickness. Brushes or lambskin roller may be used for smaller areas. Up to 100 - 200 g/m² may be applied in one operation to vertical surfaces without loss of material. The exact amount depends on the absorbency of the substrate.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.



TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

HEALTH & SAFETY INSTRUCTIONS

This product contains a biocide for the protection of the cured product. Contains 2-OCTYL-2H-ISOTHIAZOL-3-ONE. May produce an allergic reaction. For further information, please request the material safety data sheet for this product.

IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- o If frost is forecast, or in excessive wet conditions
- o When Relative Humidity is above 95%
- o In temperatures below +5°C or above +25°C
- o If the elevation is in direct sunlight
- o If the substrate is hot (at or above 30C) or below +5°C
- o Coverage rates are approx. and do not take into account wastage and uneven substrates

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.