



AP77 Flexible Smooth Masonry Paint



Technical Data

Pack Size
10L

Colours
White, Cream, Magnolia & Grey

Application Tool
Brush, Roller or Spray

Suitable Substrates
Bonded Paint & Coatings, Render, Brick, Stone, Rough-Cast & other Masonry Substrates

Primer
New Surfaces 10-50% dilution with clean water depending on the substrate

Coverage
Approximately 4-15m² per litre dependent on the nature and porosity of the surface

Application Temperature
5°C - 25°C for a minimum of 24 hours



Silicone Technology



Highly Breathable



Algae Resistant



Ultra-Waterproofing



Matt Finish



Excellent Adhesive

DESCRIPTION

WetherTex AP77 Flexible Smooth Masonry Paint is a high performance, exterior quality flexible masonry paint. Developed using advanced Otilife silicone technology for improved breathability, AP77 provides a smooth matt finish that is both self cleaning and highly weatherproof and will protect your building for up to 20 years.

PREPARATION

Ensure all surfaces to be painted are clean, dry and free from grease and loose or flaking material that may impair adhesion. Do not apply to shiny surfaces. Scaffolding must be independently tied to allow for uninterrupted application. Any faults in the substrate, particularly those that can lead to moisture penetration, must be rectified or can affect the finish quality. Mask around the area where the material is to be applied. Masking tape must be removed before the material has dried out. Ensure all BS standards are carried out through application.

APPLICATION

Stir the product thoroughly and do not contaminate. For the best results apply by brush, lamb's wool roller or spray. Application tool type and quality may influence the finished appearance. Apply liberally and avoid overspreading. To avoid dampness and discolouration painting should be avoided below DPC or within 150mm of ground level. AP77 can be diluted between 10-50% depending on the suction of the substrate.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture. If you have any left over product, ensure that you close the tin by replacing the lid firmly and securely and store in a safe place. Protect from frost. To avoid the risk of spillage, always store and transport in a secure upright position.

TOOL CLEANING

All equipment must be washed with clean, cold water immediately after use. Waste material should not be emptied in the drainage systems. Some local authorities have special facilities for the disposal of leftover paint. Please do not add any product into drains or watercourses.

HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting www.wetherTex.co.uk

IMPORTANT INFORMATION

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If frost or heavy rain is forecast
- Relative Humidity is above 85%
- In temperatures below 5°C or above +25°C
- If the substrate is hot (at above 30°C) or below +1°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

If the above is not followed or alternative products are used, then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.