



C10 Multi-surface Fungicidal Wash



Technical Data

Pack Size
5L

Application Tool
Brush, Roller or Spray

Suitable Substrates
Masonry and Wood

Coverage
Approximately 16m² per 5 litre dependent on the nature and porosity of the surface

Application Temperature
5°C - 25°C

Humidity Temperature
Less than 95%

BIOACTIVE
TEC-NOLOGY®



Long Term Protection
& Low Maintenance



Fast Acting



Algae Resistant



Bio Stop



Ready to Use



Suitable for Hand or
Spray Application

DESCRIPTION

WetherTex C10 Multi Surface Fungicidal Wash is a ready to use, water based masonry wash for the removal of a broad range of bacterial, algal and fungal growth on masonry surfaces prior to painting. Developed using fast acting bioactive tec-nology, the product is particularly effective against algae and mould growth and creates a clean surface, ready for painting.

PREPARATION

Organic growths may indicate consistently damp conditions and substandard direct sunlight. Sources of moisture should be identified and rectified to prevent recurrence. Condensation, rising damp, faulty plumbing or guttering, etc. should be considered as a possible source. Remove all loose and flaking material by cleaning the surface with a soft bristle brush. If possible, power wash the substrate with a suitable power washer.

APPLICATION

Apply C10 Multi-surface Fungicidal Wash directly onto the surface using a pressurised knapsack or garden sprayer but can be brush or roller applied. Ensure the surface is drenched in the wash and has been absorbed into the capillaries of the substrate. C10 Fungicidal Wash should be left for 24hrs to take effect and kill the growing moss and unseen spores. Dead growth should be removed by brushing with a steel brush or a suitable power washer.

Note: Do not apply C10 Multi-surface Fungicidal Wash in rain or in temperatures below 5°C.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture.

TOOL CLEANING

All equipment must be washed with clean, cold water immediately after use. Waste material should not be emptied in the drainage systems.

HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting www.wetherTex.co.uk

IMPORTANT INFORMATION

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If frost or heavy rain is forecast
- Relative Humidity is above 95%
- In temperatures below 5°C or above +25°C
- If the substrate is hot (at above 30°C) or below +1°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discolouration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

If the above is not followed or alternative products are used, then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.