



SR72 Smart Cream *Nano*



Technical Data

Pack Size
25kg

Application Temperature
5°C - 25°C

Application Tool
Brush, Roller or Spray

Humidity
Less than 95%

Suitable Substrates
Concrete, Brick, Stone and Renders

Coverage
Approximately 5-10m² per kg



Long Term Protection
& Low Maintenance



Energy Saving



Waterproofing



Nano Technology



Highly Polymer
Modified



Water Repellent

DESCRIPTION

Wethertex SR72 WetherDry Smart Cream Nano is an aqueous based hydrophobic impregnating agent based on an innovative nano scale fluoropolymer technology. SR72 is a high quality speciality product for hydrophobic impregnation of natural mineral substrates.

PREPARATION

All surfaces should be clean, reasonably dry and free from algae, lichen & other growths and grease. If there is evidence of organic growth, power wash to remove & apply Wethertex C10 Fungicidal Wash in accordance with instructions.

MIXING

SR72 WetherDry Smart Cream Nano is supplied ready to use.

APPLICATION

SR72 WetherDry Smart Cream Nano is best applied to the mineral substrate by the airless technique, undiluted and in the desired thickness. Brushes or lambskin roller may be used for smaller areas. Up to 100 - 200 g/m² may be applied in one operation to vertical surfaces without loss of material. The exact amount depends on the absorbency of the substrate.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture.

TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied in the drainage systems.

HEALTH & SAFETY INSTRUCTIONS

This product contains a biocide for the protection of the cured product. Contains 2-OTYL-2H-ISOTHIAZOL-3-ONE. May produce an allergic reaction. For further information, please request the material safety data sheet for this product by visiting www.wetherby.co.uk

IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- If frost is forecast, or in excessive wet conditions
- Relative Humidity is above 95%
- In temperatures below +5°C or above +25°C
- If the elevation is in direct sunlight
- If the substrate is hot (at above 30°C) or below +5°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discolouration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

If the above is not followed or alternative products are used, then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any applicator involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for the specific application if no specification has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.