



PP1 Pre-prep Primer



Technical Data

Pack Size
10L

Application Tool
Brush, Roller or Spray

Suitable Substrates
GRC, X71, Bonded Paint, Dash, Roughcast, Render

Drying Time
3 - 24 hours @ -5°C – 25°C

Coverage
Approximately 8-9m² per litre

Application Temperature
-5°C – 25°C for a minimum of 24 hours

Humidity
Less than 95% for a minimum of 24 hours



Extra Coverage



Roller, Brush or Spray Application



High Adhesive



Low Temperature Application



Highly Polymer Modified



Water Repellent

DESCRIPTION

WetherTex PP1 Pre-prep Primer is a ready mixed, flexible, through coloured penetrating primer to control suction and ensure good key, prior to the application of MP44 Spray Wall Coating or AX1 Pliolite Thin Coat Render.

PREPARATION

All surfaces must be sound, clean, dry and free of any material which may impair adhesion. Scaffolding must be independently-tied to allow for uninterrupted application. Any faults in the structure, particularly those which may lead to moisture penetration, must be rectified.

MIXING

PP1 Pre-prep Primer is supplied ready to use, but may need re-mixing using a suitable paddle mixer to regain correct consistency for application.

APPLICATION

By roller – submerge the roller totally in the primer to ensure that the roller is fully loaded with material to allow even application without spreading too thinly.

Specification Clauses relating to this product can be found in NBS Section M20 Rendering. BS 5262 Code of Practice for External Rendering and BS 8000-10 must be followed.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture.

TOOL CLEANING

All equipment must be washed with clean white spirit immediately after use. Waste material should not be emptied in the drainage systems.

HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting www.wetherTex.co.uk

IMPORTANT INFORMATION

The weather conditions for application and drying are critical. Do not apply if any of the following conditions are likely to arise during - or in the first 24 hours following application:

- If frost is forecast, or in excessive wet conditions
- Relative Humidity is above 95%
- In temperatures below -5°C or above +25°C
- If the elevation is in direct sunlight
- If the substrate is hot (at above 30°C) or below +1°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discolouration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any applicator involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for the specific application if no specification has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.