

# LD77

## Pliolite Light Texture Coating

### Safety Data Sheet

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. PRODUCT IDENTIFIER

**Product name:** WETHERTEX LD77 PLIOLITE LIGHT TEXTURE WALL COATING  
**Product code:** WT0008

##### 1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

**Use of substance / mixture:** Material used in the construction industry.  
PC9a: Coatings and paints, thinners, paint removers.

##### 1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Company name:** Wetherby Group, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE, United Kingdom  
**Tel:** 01845 578555  
**Fax:** 01845 578777  
**Email:** technical@wetherbygroup.com

##### 1.4. EMERGENCY TELEPHONE NUMBER

#### SECTION 2: Hazards identification

##### 2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

**Classification under CLP:** *STOT RE 1:* H372; *Aquatic Chronic 3:* H412; *Flam. Liq. 3:* H226; *STOT SE 3:* H336

**Most important adverse effects:** Flammable liquid and vapour. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

##### 2.2. LABEL ELEMENTS

**Label elements:**  
**Hazard statements:**

**H226:** Flammable liquid and vapour.  
**H336:** May cause drowsiness or dizziness  
**H372:** Causes damage to organs through prolonged or repeated exposure.  
**H412:** Harmful to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:**

**GHS02:** Flame  
**GHS07:** Exclamation mark  
**GHS08:** Health hazard



##### Precautionary statements:

**P210:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**P241:** Use explosion-proof equipment.

**P260:** Do not breathe dust/fumes/gas/mist/vapours/spray.

**P280:** Wear protective gloves/protective clothing/eye protection/face protection.

**P303+P361+P353:** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**P304+P340:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### 2.3. OTHER HAZARDS

**Other hazards:** In use, may form flammable/explosive vapour-air mixture

**PBT:** This product is not identified as a PBT/vPvB substance.

**SECTION 3: Composition/information on ingredients**

**3.2. MIXTURES**

**HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) - REACH registered number(s): 01-2119458049-33-XXXX**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
919-446-0	-	-	Flam. Liq. 3: H226; Aquatic Chronic 2: H411; STOT SE 3: H336; STOT RE 1: H372; Asp. Tox. 1: H304	10-30%

**HYDROCARBONS, C9, AROMATICS**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
918-668-5	-	-	Flam. Liq. 3: H226; STOT SE 3: H335; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; STOT SE 3: H336	1-10%

**2-BUTOXYETHANOL - REACH registered number(s): 01-2119475108-36-XXXX**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%

**SECTION 4: First aid measures**

**4.1. DESCRIPTION OF FIRST AID MEASURES**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.  
**Ingestion:** Wash out mouth with water. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED**

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.  
**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED**

**Immediate / special treatment:** Eye bathing equipment should be available on the premises. A decontamination shower should be available on the premises. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

## SECTION 5: Fire-fighting measures

### 5.1. EXTINGUISHING MEDIA

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

### 5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. ADVICE FOR FIRE-FIGHTERS

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## SECTION 6: Accidental release measures

### 6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. ENVIRONMENTAL PRECAUTIONS

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. REFERENCE TO OTHER SECTIONS

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## SECTION 7: Handling and storage

### 7.1. PRECAUTIONS FOR SAFE HANDLING

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. SPECIFIC END USE(S)

**Specific end use(s):** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. CONTROL PARAMETERS

**Hazardous ingredients: 2-BUTOXYETHANOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50ppm	-	-

### DNEL/PNEC VALUES

**Hazardous ingredients:**

**HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	330mg/m <sup>3</sup>	Workers	Systemic
DNEL	Dermal	44mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	71mg/m <sup>3</sup>	Consumers	Systemic
DNEL	Dermal	26mg/kg bw/day	Consumers	Systemic

**HYDROCARBONS, C9, AROMATICS**

Type	Exposure	Value	Population	Effect
DNEL	Dermal	25mg/kg/day	Workers	Systemic
DNEL	Inhalation	150mg/m <sup>3</sup>	Workers	Systemic
DNEL	Oral	11mg/kg/day	Consumers	Systemic
DNEL	Inhalation	32mg/m <sup>3</sup>	Consumers	Systemic

### 8.2. EXPOSURE CONTROLS

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Also soluble in:** Soluble in white spirit and solvent naptha (mineral fillers insoluble).

**Viscosity:** Viscous

**Viscosity test method:** Brookfield

**Boiling point/range°C:** >140°C

**Melting point/range°C:** No data available.

**Flammability limits %:**

lower: 0.7

upper: 7

**Flash point°C:** >40°C

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** >230°C

**Vapour pressure:** No data available.

**Relative density:** 1.45 - 1.50g/mL

**pH:** No data available.

**VOC g/l:** 378

### 9.2. OTHER INFORMATION

**Other Information:** No data available

## SECTION 10: Stability and reactivity

### 10.1. REACTIVITY

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. CHEMICAL STABILITY

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. POSSIBILITY OF HAZARDOUS REACTIONS

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. CONDITIONS TO AVOID

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. INCOMPATIBLE MATERIALS

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

**Haz. decomp. products:** In combustion emits toxic fumes.

## SECTION 11: Toxicological information

### 11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

**Hazardous Ingredients: HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)**

DERMAL	RAT	LD50	>3400	mg/l
ORAL	RAT	LD50	>15000	mg/kg
VAPOURS	RAT	4H LC50	>13100	mg/l

**HYDROCARBONS, C9, AROMATICS**

DERMAL	RBT	LD50	>3160	mg/kg
ORAL	RAT	LD50	3592	mg/kg

**2-BUTOXYETHANOL**

IN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

**Relevant hazards for substance:**

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### SYMPTOMS / ROUTES OF EXPOSURE

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## SECTION 12: Ecological information

### 12.1. TOXICITY

**Ecotoxicity values:** No data available.

### 12.2. PERSISTENCE AND DEGRADABILITY

**Persistence and degradability:** Biodegradable.

### 12.3. BIOACCUMULATIVE POTENTIAL

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. MOBILITY IN SOIL

**Mobility:** Readily absorbed into soil.

### 12.5. RESULTS OF PBT AND vPvB ASSESSMENT

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. OTHER ADVERSE EFFECTS

**Other adverse effects:** Negligible ecotoxicity.

## SECTION 13: Disposal considerations

### 13.1. WASTE TREATMENT METHODS

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## SECTION 14: Transport information

### 14.1. UN NUMBER

**UN number:** UN1263

### 14.2. UN PROPER SHIPPING NAME

**Shipping name:** PAINT RELATED MATERIAL

### 14.3. TRANSPORT HAZARD CLASS(ES)

**Transport class:** 3

### 14.4. PACKING GROUP

**Packing group:** III

### 14.5. ENVIRONMENTAL HAZARDS

**Environmentally hazardous:** Yes

**Marine pollutant:** No

### 14.6. SPECIAL PRECAUTIONS FOR USER

**Special precautions:** No special precautions.

## SECTION 15: Regulatory information

### 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

**Specific regulations:** Not applicable.

### 15.2. CHEMICAL SAFETY ASSESSMENT

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## SECTION 16: Other information

### Other information:

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

### Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

### Phrases used in s.2 and s.3:

**H226:** Flammable liquid and vapour.

**H302:** Harmful if swallowed.

**H304:** May be fatal if swallowed and enters airways.

**H312:** Harmful in contact with skin.

**H315:** Causes skin irritation.

**H319:** Causes serious eye irritation.

**H332:** Harmful if inhaled.

**H335:** May cause respiratory irritation.

**H336:** May cause drowsiness or dizziness.

**H372:** Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**H411:** Toxic to aquatic life with long lasting effects.

**H412:** Harmful to aquatic life with long lasting effects.