



## SP77 Ultra-Life Smooth Masonry Paint



### Technical Data

**Pack Size**  
10L

**Colours**  
White and a wide range of colours

**Application Tool**  
Brush, Roller or Spray

**Suitable Substrates**  
Bonded Paint & Coatings, Render, Brick, Stone, Rough-Cast & other Masonry Substrates

**Primer**  
New Surfaces 10-50% dilution with clean water depending on the substrate.

**Coverage**  
Approximately 4-15m<sup>2</sup> per litre dependent on the nature and porosity of the surface

**Application Temperature**  
5°C - 25°C for a minimum of 24 hours



Silicone Technology



Matt Finish



Highly Breathable



Ultra-Waterproofing



Self-Cleaning



Excellent Adhesive

### DESCRIPTION

WetherTex SP77 Masonry Paint is a premium quality Silicone resin based ready to use high performance through coloured paint that is highly vapour permeable. Designed to give an ultra-high weatherproof finish whilst allowing the substrate to breathe. Excellent coverage rates dependant on the substrate, with outstanding covering power.

### PREPARATION

Ensure all surfaces to be painted are clean, dry and free from grease and loose or flaking material that may impair adhesion. Do not apply to shiny surfaces. Scaffolding must be independently tied to allow for uninterrupted application. Any faults in the substrate, particularly those that can lead to moisture penetration, must be rectified or can affect the finish quality. Any existing crazed or flaking paint, dirt, grease or other surface contaminants should be removed. Mask around the area where the material is to be applied. Masking tape must be removed before the material has dried out. Ensure all BS standards are carried out through application. Ensure a thorough assessment of the substrate is conducted prior to application.

### APPLICATION

Stir the product thoroughly, do not contaminate. For the best results apply by brush, roller or spray. Application tool type and quality may influence the finished appearance. SP77 can be diluted between 10-50% depending on the suction of the substrate. It is recommended to apply a diluted coat first to prime the surface. Apply liberally and avoid overspreading. To avoid dampness and discolouration painting should be avoided below DPC or within 150mm of ground level. Apply with paintbrush, or lamb's wool roller or spray depending on the size of the substrate.

### STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture. If you have any leftover product, ensure that you close the tin by replacing the lid firmly and securely and store in a safe place. Protect from frost. To avoid the risk of spillage, always store and transport in a secure upright position.

### TOOL CLEANING

All equipment must be washed with clean, cold water immediately after use. Waste material should not be emptied in the drainage systems. Some local authorities have special facilities for the disposal of leftover paint. Please do not add any product into drains or watercourses.

### HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting [www.wetherTex.co.uk](http://www.wetherTex.co.uk)

### IMPORTANT INFORMATION

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If frost or heavy rain is forecast
- Relative Humidity is above 85%
- In temperatures below 5°C or above +25°C
- If the substrate is hot (at above 30°C) or below +1°C
- Coverage rates are approximate and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discolouration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

If the above is not followed or alternative products are used, then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.