



MS11 Multi-Surface Renovation Paint

WTDS/MS11/0220

Technical Data

Pack Size
5 Litre

Colours
Wide Range of Colours

Application Tool
Brush, Roller or Airless Spray

Application Temperature
8°C - 25°C

Humidity Temperature
Less than 85%

Suitable Substrates

Steel, Aluminum, Galvanized steel, Ceramic tile (not showers/wet rooms), PVC, Wood, Brick, Concrete Block, Stone, Plaster, Pre-cast concrete, Render, Fibre cement board, Plaster boards, Calcium silicate boards Any surface where great adhesion, fast drying, good coverage is required

Coverage

Approximately 12 to 15 m² / Litre per coat dependant on the nature and porosity of the surface. Rough surfaces will significantly reduce the coverage rates



Long Term Protection



Highly Breathable



Self Priming



Water Repellent



Highly Durable



Excellent Adhesive

DESCRIPTION

WetherTex MS11 Multi-Surface Renovation Paint is a high performance protective coating providing a decorative satin finish. It has superb adhesion to multiple substrates while being highly vapour permeable and water-shedding. This versatile, hard wearing paint for both interior and exterior application is also self priming and resistant to flash rust.

PREPARATION

Ensure all surfaces to be painted are clean, dry and free from grease, loose or flaking material and any other contaminants that may impair adhesion. Any faults in the substrate, particularly those that can lead to moisture penetration, must be rectified or can affect the finish quality. If your substrate has been previously painted rub down with a fine waterproof abrasive paper and then rinse thoroughly. Bare substrates should also be abraded in a similar manner to allow improved adhesion. To improve inter-coat adhesion, repeat between all additional coats. Hard wall plasters should be scored with a coarse glass-paper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

APPLICATION

Apply by brush, roller, conventional H.V.L.P or airless spray. Stir well and check colour before use. Do not apply at air or surface temperatures below 8°C or when likely to rain before the paint has fully dried.

Stir the product thoroughly to ensure it is fully homogeneous, do not contaminate. For the best results apply by brush, roller or spray. Application tool type and quality may influence the finished appearance. Apply liberally and avoid overspreading. Not to be applied below 8°C. Under normal conditions the coating will be touch dry after 1 hour. Overcoating time for subsequent coats is 3-4 hours. Ensure good ventilation during drying and application. Porous surfaces should be sealed with a first coat of MS11 Multi-Surface Renovation Paint thinned with up to 20% clean water. On sealed surfaces apply two to three coats, allowing each coat to dry thoroughly.

Spraying can considerably reduce the coverage rate depending on the type of spray equipment used.

Not suitable for areas under constant water contact such as shower cubicles or areas of high traffic such as worktops and handrails. Substrates which have had water-repellent preservative treatments applied should be avoided because adhesion could be compromised. Can be

used on glass internally but not externally. Not recommended for horizontal decking areas and floors. Hot surfaces such as radiators should be coated when cold and allowed to dry before resuming heat.

Paint will be fully hardened after 1 month.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture. If you have any left over product, ensure that you close the tin by replacing the lid firmly and securely and store in a safe place. PROTECT FROM FROST. To avoid the risk of spillage, always store and transport in a secure upright position.

TOOL CLEANING

All equipment must be washed with clean, cold water immediately after use. Waste material should not be emptied in the drainage systems. Some local authorities have special facilities for the disposal of leftover paint. Please do not add any product into drains or watercourses.

HEALTH & SAFETY INSTRUCTIONS

For further information, please request the material safety data sheet for this product by visiting www.wetherTex.co.uk



MS11 Multi-Surface Renovation Paint WTDS/MS11/0220

IMPORTANT INFORMATION

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If frost or heavy rain is forecast or wet conditions
- If relative humidity is above 85%
- If temperatures are below 8°C or above +25°C
- If the substrate is hot (at above 30°C) or below +1°C

If the above is not followed or alternative products are used, then system failure may occur.

Coverage rates are approximate and do not take into account wastage and uneven substrates

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no specification has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.