



PP77 All Weather Pliolite Masonry Paint - Smooth or Textured Finish CE WTDS/PP77/0121

<p><b>Technical Data</b></p> <p><b>Pack Size</b> 5 litre, 10 litre</p> <p><b>Colours</b> Wide Range of Colours</p> <p><b>Application Tool</b> Brush, roller &amp; spray</p> <p><b>Suitable Substrates</b> Bonded Paint &amp; Coatings, Render, Brick, Stone, Rough-Cast &amp; other Masonry Substrates</p>	<p><b>Coverage</b> Approximately 4-15m<sup>2</sup> / litre (Dependant on the nature and porosity of the surface)</p> <p><b>Application Temperature</b> -5°C to 25°C for a minimum of 24 hours</p> <p><b>Humidity Requirement</b> Less than 85%</p>	<div style="display: flex; flex-wrap: wrap; justify-content: space-around;"> <div style="text-align: center; width: 30%;">  <p>Apply down to -5°C</p> </div> <div style="text-align: center; width: 30%;">  <p>Breathable</p> </div> <div style="text-align: center; width: 30%;">  <p>Rain Resistant in 20 min</p> </div> <div style="text-align: center; width: 30%;">  <p>Excellent Adhesion</p> </div> <div style="text-align: center; width: 30%;">  <p>Highly Water Resistant</p> </div> <div style="text-align: center; width: 30%;">  <p>Matt Finish</p> </div> </div>
--	--	--

**DESCRIPTION**

WetherTex PP77 All Weather Pliolite Masonry Paint is a premium, solvent borne coating that is brush, roller or spray applied. Formulated using Pliolite Technology, it has excellent adhesion and can be applied in temperatures as low as -5°C allowing for all year round application. Available in a smooth or textured finish.

**PREPARATION**

Make good cracks and structural defects. All surfaces must be clean, dry and free from algae, lichen & other growths. Any faults in the substrate, particularly those that can lead to moisture penetration, must be rectified or can affect the finish quality. Any existing crazed or flaking paint, dirt, grease or other surface contaminants should be removed. If there is evidence of organic growth power wash to remove and apply WetherTex C10 Fungicidal Wash in accordance with manufacturer's instructions.

**APPLICATION**

Stir the product thoroughly, do not contaminate. PP77 All Weather Pliolite Masonry Paint can be applied down to -5°C by brush, short pile roller or spray. After suitable preparation apply two coats. Product may be thinned by no more than 10% for use as a penetrating base coat on very porous surfaces. Do not thin for normal application (Use clean White Spirit).

**STORAGE**

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from the date of manufacture. If you have any leftover product, ensure that you close the tin by replacing the lid firmly and securely and store in a safe place. To avoid the risk of spillage, always store and transport in a secure upright position.

**TOOL CLEANING**

All equipment must be washed with clean white spirit immediately after use. Waste material should not be emptied into drainage systems. Some local authorities have special facilities for the disposal of leftover paint. Please do not add any product into drains or watercourses.

**HEALTH & SAFETY INSTRUCTIONS**

For further information, please request the material safety data sheet for this product by visiting [www.wetherTex.co.uk](http://www.wetherTex.co.uk)

**IMPORTANT INFORMATION**

The environmental climatic conditions for application and drying are critical. The following conditions can negatively affect the product performance and should be avoided, and taken into full consideration in the first 24 hours after application:

- If heavy rain is forecast, or wet conditions
- Relative Humidity is above 85%
- In temperatures below -5°C or above +25°C
- If the elevation is in direct sunlight
- If the substrate is hot (at or above 30°C) or below +1°C

Coverage rates are approx. and do not take into account wastage and uneven substrates

The product must be protected against heavy rain, direct sun or wind in the first 24 hours after application. Sheeting the façade or the scaffold is advised to protect against this. For this particular product if these parameters are not met polymer film damage, wash off, discoloration and potential failure can occur. It is the responsibility of the application contractor to manage and record the weather conditions during application and curing of the product.

If the above is not followed or alternative products are used; then system failure may occur.

To the best of our knowledge and belief, this information is true and accurate. However, as conditions of use of the product and the expertise of any labour involved are beyond our control, the end user must satisfy themselves by prior testing that the product is suitable for their specific application if no spec has been provided for the project in hand. No responsibility can be accepted, nor any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that they have consulted our latest literature.